



# Smoke Alarm

S-9102

## Description

S-9102 Smoke Alarm is designed for domestic usage such as a house, villa and apartment, etc. Built with high-quality components and advanced technology, the alarm has an excellently stable performance and low power consumption. A 9V battery will operate up to one year. It can be easily installed, no commission required. Utilize internal buzzer to provide a loud local alarm.

## Technical Specifications

- Test Certificate: CE EMC AE50121029
- Power Supply: PP3 (H6F22) DC9V battery
- Indicator: Red flashes in every 50 seconds in normal condition.
- Output Interface: Available for optional use
- Network Output: Maximum 30 alarm in one system, available for optional use.
- Photoelectric Output: 5mA /30VDC, Optional
- Sound level : 80dB
- Detection Area: 40m<sup>2</sup>
- Operating Environment:
- Temperature: -10<sup>o</sup> ~ +50<sup>o</sup>
- Relative Humidity: 95%
- Dimension: 140 x 54mm(D x H, with base)
- Material and Color: ABS white
- Weight: 235g
- Mounting Hole Distance: 50mm~108mm

## Features and Benefits

- Self contain Optical Smoke detector and alarm sounder
- With test and reset button
- 9v operated
- Low battery indication
- Battery removable will inhabit cover from closing ( as per UL standard)
- Easy installation
- LED indicator for 360<sup>o</sup> vision
- Output to interface with other security equipment

## Detector Installation and Wiring

The Smoke Alarm should be installed in compliance with all local codes having a jurisdiction in your area or NFPA 72 National Fire Alarm Code, NFPA 70 National Electrical Code, BS 5389 and EN54. For information about installation refers to manual.

## Ordering Information



**Part Number:** S-9102  
**Description:** Smoke Alarm  
**Weight / Kg.:** 0.300  
**Pack Qty. per Box:** 30

